

SMOKE AND CARBON MONOXIDE DETECTOR REQUIREMENTS.

For questions on proper installation, call Fire Prevention 617-539-5813

CARBON MONOXIDE DETECTORS MUST BE INSTALLED WITHIN TEN FEET OUTSIDE OF THE BEDROOM DOORS

AND IN THE BASEMENT.

Below is a list of basic smoke alarm requirements, for one- and two-family homes smoke alarms must be installed.

- 1. On every habitable level and in the basement.
- 2. Inside every bedroom (MA state building code 780 CMR)
- 3. On the ceiling at the base of each stairway leading to a floor above.
- 4. For 2 or more family, in the common areas shared by residents.
- Smoke alarms must be photoelectric, may be in combination with ionization or carbon monoxide alarms.
- 6. All battery powered alarms must be 10 years, sealed, non-rechargeable, non-replaceable battery type. If we have access to the battery you will fail the inspection.
- 7. Attached garage must have hard wired heat detector. (MA state building code 780 CMR)
- 8. Battery powered alarms over ten years old must be removed and replaced

AVOID CODE VIOLATIONS:

- 1. No keyed bedroom locks
- 2. All means of egress clear of debris
- 3. Make sure the street number is visible from the street. (MGL c148)

3 to 5-unit occupancies, require hard wired, interconnected detectors in common stairways and basement

6- unit and up, it also requires:

- 1. Fire alarm panel.
- 2. Master box preferred over 12 units.
- 3. Knox box installed at the front entrance.
- 4. Residential occupancies require an annual Fire Alarm inspection to be completed by a licensed Fire alarm technician. Proof of a current, active inspection completed within the last twelve months is required to be provided to the Fire Inspector on the day of the inspection.